

Technical data sheet

FV130.2

Execution for: South Korea

Utensil washer

Programme start button: right
Working height: 845 mm
3-phase current: 3N PE 400V 60Hz
Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2016

Sample illustration

Technical data

| | |
|---------------------------------|---|
| Rack capacity/h (theoretical) | 30 / 15 / 10 racks/h |
| Programme cycle time | 120 / 240 / 360 s |
| Rack dimension | 850 x 700 mm |
| Entry height | 740 mm |
| Dimensions (W x H x D) | 1030 x 1785 x 895 mm |
| Electrical feeding cable | 3-phase current 3N PE 400V 60Hz* nominal capacity: 14.6 kW nominal current: 25.3 A |
| Protection class of the machine | IP X5 |
| Equipment | MIKE 2 control Infrared interface for wireless communication Leakage detector Soft start Wash arm drive Boiler safety device Drain pump Automatic self-cleaning when tank is drained Aqua-Stop system Back wall cladding |
| Fresh water line | Air gap 'AA' in accordance with EN 1717 with booster pump |
| Fresh water supply | Minimum flow pressure 60 kPa / 0.6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5.0 bar Max. supply water temperature 60 °C |
| Flow rate | 5.0 l/min |
| Final rinse water quantity | 5.8 liters/cycle |

Technical data sheet

| | |
|---|---|
| Boiler | Contents: 18.0 l Heater: 12.00 kW Temperature: 83 °C Tank / boiler locked |
| Wash tank | Filling: 85.0 l Heater: 6.00 kW Temperature: 60 °C |
| Wash pump | Performance: 2.20 kW |
| Dosing of rinse aid | Hose pump (24 V) with time control and suction lance |
| Material | Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404 |
| Heat emission | for 15 programme cycles/h total: 4.5 kW perceptible: 3.0 kW latent: 1.5 kW |
| Ventilation flow rate | 1150 m³/h |
| Steam emission | 2.1 kg/h |
| Emission sound pressure level at the workplace (LpA) | 69 dB |
| Net weight | 270.0 kg |

***Note:**

Electrical equipment suitable for supply voltage:
3N PE 400 V 60 HZ (3N PE 380-415 V 60 Hz)