
1.0	machine connection: drain connection hose, DN 22 hose fitted as odour trap in interior of machine
1.1	drain (max. 700 mm above finished floor level), DN 50
2.0	Machine connection: fresh water supply, G 3/4"
2.2	Soft cold water 10°C, DN 15, G 3/4 a
	max. 0,54 mmol/l CaCO₃ (max. 3°dH)
	Flow rate: 5 l/min
	Minimum flow pressure: 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar
	stopcock and fine screen ≤ 25 μm
3.0	Machine connection: electrical connection cable 5G 2,5mm²
3.1	electricity supply to the machine: 3N PE 400V ~ 50Hz
	nominal current / - capacity: 16,0 A / 6,9 kW
	Fuse protection: 16 A
	♦ Voltage equalising cable
	The master switch must be provided on site
	Electrical equipment suitable for supply voltage:
	3N PE 380-415 V 50 Hz / 1N PE 220-240 V 50 Hz
6.0	Heat load of warewash area
6.1	for 20 programme cycles/h
	total 2,1 kW, perceptible 1,4 kW, latent 0,7 kW
all cables, pipes etc leaving machine 1,6 m	
the position of the connection piping can also be mirror-inverted!	
Machine Equipment	
(A) Entry height	
(D) Rinse agent pipe and suction lance	





MEIKO AUSTRIA GMBH HETMANEKGASSE 1B, A-1230 WIEN
TEL. +43 1 6992039 TELEFAX +43 1 699203923
E-MAIL: office@meiko.at

This drawing may not be neither passed to third parties for their information or copied or used for competitive purposes without our consent. All rights reserved. We reserve the right to make changes resulting from technical progress. This drawing was computer generated and is not subject to the checking and any release process; it is also not subject to change

This document is only valid in conjunction with the conditions defined in Supplementary Sheet "Important Information". These can be requested from the manufacturer or downloaded from the Partnernet.

Revision

Reference UPSTER U 500G DISHWASHER STANDARD DRAWING / HUN M2

TYPE: GLASSES

ΕN

Drawing-No. S00089419

Scale drawn: 1:25

13.08.2020 m-iplan

checked: 13.08.2020 m-iplan

Order-No.

COPYRIGHT by MEIKO

(E) Detergent dosing unit with suction lance